FEE SCHEDULE:

ANDOVER TOWNSHIP

SIGNED:

FIRE OFFICIAL

(does not include the day the application was received)

134 NEWTON-SPARTA ROAD, NEWTON, NJ 07860

11 or more business days:

\$35

Andover Township

APPLICATION FOR ONE & TWO FAMILY DWELLING CERTIFICATION OF

5 to 10 business days days: Less than 4 business days:

\$70 \$125

SMOKE DETECTOR, CARBON MONOXIDE DETECTOR AND FIRE EXTINGUISHER COMPLIANCE

Re-Inspection for Failure:

PART I - To be completed and returned to abo Dwelling Location: Block: Lot:			er Township
I,, as owner or an auth	orized representative of the	e owner, hereby request an i	nspection of
the above referenced location for the purpose extinguisher compliance.	of obtaining a certification	of smoke detector, carbon m	onoxide alarm and fire
Date of Application:	Hom	e Number:	
Name of Contact Person:		Number:	
Closing Date:			<u> </u>
PART II – To be completed by homeowner or	homoownor's agent		
This is a story dwelling			
□ with a basement □ with a fuel burn □ without a basement □ without a fuel burn □ without a basement □ without a fuel burn	ning appliance uwith	an attached garage	
□ without a basement □ without a fuel b	ourning appliance	out an attached garage	
I,, certify that the dwe	elling at the above reference		cors installed as follows:
☐ On each level of the dwelling, including base			
☐ Outside each separate sleeping area (within		and	
☐ All smoke detectors are in working order	,,		
Smoke detectors required above shall be listed	l in accordance with ANSI/I	JL-217 and located and mai	ntained in accordance with
NFPA 72. Detectors shall be mounted on the ce			
not less than 4 inches, or more than 12 inches,	below the ceiling at its high	nest point. The detectors are	not required to be
interconnected. Battery powered detectors r			
multiple-station smoke alarms installed as par			
battery powered smoke alarms. See diagrams			
installation of smoke detectors. If Smoke Dete	ectors are older than 10 <u>y</u>	ears (Date on Back) includ	ing AC Powered, they must be
<u>replaced.</u> I further certify that carbon monoxide alarm :	s ara		
Truitiler certify that carbon monoxide alarms	s are.		
☐ Installed and working in the immediate vicin	ity of each sleeping area (w	vithin 10 feet of each bedroo	m
☐ A carbon monoxide alarm is not required sin			
Carbon monoxide alarms shall be listed and lal			
720. They may be battery-operated, hard-wire	d and of the plug-in type ar	nd can be mounted on the co	eiling or wall at any
height except the 4 inches of dead air space wh	here the wall meets the ceil	ing.	
The Legislature amended and enacted P.L. 199			
change of occupancy be provided with a porta			
monoxide detectors. The requirements for the			
\square At least one portable fire extinguisher shall			
□ The extinguisher must be less than one year			-
□ The size shall be <u>no smaller than 2A.10B.C</u>	<u>, rated for residential us</u>	e and weigh no more than	10 lbs.
$\hfill\Box$ The hangers or brackets supplied by the ma	nufacturer must be used;		
$\hfill \square$ The extinguisher must be located within 10	feet of the kitchen;		
☐ The top of the extinguisher must not be mor	e than 5 feet above the floo	or;	
☐ The extinguisher must be visible and in a re	adily accessible location, fr	ee from being blocked by fu	rniture, storage or
other items;			
☐ The extinguisher must be accompanied by a	n owner's manual or writte	en information regarding th	e operation, inspection,
and maintenance of the extinguisher; and			
☐ Lastly, the extinguisher must be installed wi	th the operating instructio	n clearly visible.	
Applicant's Signature	Print/Type Name	 Da	te
- 0	2/ -) L 2		<u></u>
PART III - CERTIFICATION OF COMPLIANCE			
THE ABOVE DWELLING HAS BEEN INSPECTED AND			
REQUIREMENTS OF THE NEW JERSEY UNIFORM FILE CARRON MONOYIDE DETECTORS AN			LE DE TECTORS,
CARBON MONOXIDE DETECTORS AN	NDFIRE EXTIN	GUISHEKS INSTALLED.	
PERMIT FEE PAID: 🗆 CASH 🗆 CHECK NO	Amount:	Received:	*Please make checks
SIGNED.	DATE.		payable to;
TI IN E I I ·	DATE.		F / /

(EXPIRES IN 6 MONTHS, NON-TRANSFERABLE)

WHERE NOT TO LOCATE DETECTORS: To avoid false alarms and/or improper operation, avoid installation of smoke detectors in the following areas:

- > Kitchens smoke from cooking may cause a nuisance alarm.
- ➤ Bathrooms excessive steam from a shower may cause a nuisance alarm.
- ➤ Near forced air ducts used for heating or air conditioning air movement may prevent smoke from reaching detector.
- ➤ Near furnaces of any type air and dust movement and normal combustion products may cause a nuisance alarm.
- > The 4 inch "Dead Air" space where the ceiling meets the wall, as shown in Figure 5.
- ➤The peak of an "A" frame type of ceiling "Dead Air" at the top may prevent smoke from reaching detector.

FURTHER INFORMATION ON DETECTOR PLACEMENT: For further information about smoke detector placement, consult the National Protection Association's Standard No. 74-1984, titled "Household Fire Warning Equipment." For Carbon monoxide alarms, their publication is Recommended Practice #720. These publications may be obtained by writing to the Public Sales Department National Fire Protection Association, Batterymarch Park, Quincy, MA 02269.

CARBON MONOXIDE ALARMS are to be located in every separate sleeping area per NFPA 720 and manufacturer's recommendations.




Figure 1

- X Smoke Detector
- O Carbon Monoxide Alarm







Figure 3







- X Smoke Detector
- O Carbon Monoxide Alarm